Specification for Approval
产品承认书

Customer:	
Customer P/N:	
VOOHU P/N:	WHSM24707D0
Version No.:	V0.1
Description:	10G BASE-T
	Laser Marking

SUZHOU VOOHU Company Approval		**Customer Approval (客户承认签章)**
DRAWN	Geoffrey.Song	
CHECKED	Sunny.Xu	
APPROVED	Elvis. Song	
日期DATE:2026/10/09		日期DATE: 2026/10/09

Please Return One Copy to Us After Approved,TKs!（承认后请回寄一份,谢谢）


VOOHU 沃虎
选沃虎 · 真靠谱
苏州沃虎电子科技有限公司
SuZhou Voohu Electronic Tech.Co.,Ltd

地址：江苏省苏州市吴江区开平商务中心G栋13楼
ADD: Building A, Alpha Building, Wujiang District,
Suzhou City, Jiangsu Province
TEL: 400 1048 018
+86 13338655578
WEB: www.voohu.cn
E-MAIL: wohu@wohu-tek.com


Revision History

Revision	Changed Date	Request By	Change Content
V0.1	2026/10/09	Arley	New Version Release

A. MECHANICAL(unit:mm)



B. SCHEMATICS




C. ELECTRICAL SPECIFICATIONS @25°C

Unless Otherwise Specified, Testing is Performed at 25°C ± 5°C


1. OCL: 120 uH Min @100KHz 0.1V
2. Leakage Inductance: 0.5uH Max @ 100KHz, 0.1V
3. DCR: 900mΩ Max
4. Turns Ratio: 1CT:1CT±5%
5. Insertion Loss: -1.2dB max @ 1~200 MHz
   -1.5dB max @ 200~300 MHz
   -2.0dB max @ 300~400 MHz
   -3.0dB max @ 400~500 MHz
6. Return Loss: -18 dB Min @ 1~100 MHz
   -16 dB Min @ 100~200 MHz
   -12 dB Min @ 200~300 MHz
   -10 dB Min @ 300~400 MHz
   -8 dB Min @ 400~500 MHz
7. Cross Talk: -25 dB Typ @ 1-500 MHz
8. Common Mode Rejection: -25 dB Typ @ 1-500 MHz
9. Isolation Hipot: 3000VAC 1mA 2S
10. Operating temperature -40℃ to +85℃
11. Storage temperature -40℃ to +85℃


D. RECOMMEND REFLOW SOLDERING CURVE




MSL:
Grade: 1 level. Floor life: 0.5 year Condition:</=30°C/60%RH.
Ramp up rate=3°C/s max Ramp down rate=6°C/s max
TL=217°C tL=60s-150s Tp=250+/-3°C Time within 3°C of actual Peak Temperature (tp): 20~40s
Ts min=150°C Ts max=200°C Ts min to Ts max: 60s-180s, 25°C to peak Temperature: 8minutes max

E. PACKAGE INFORMATION








Two Reel

Inner Carton



Five Inner Carton

Export Carton

Package Quantity:

One Reel=350Pcs

One Inner Carton=350*2=700Pcs

One Export Carton=700*5=3500Pcs